

CONTRACT SPECIFICATIONS
NEW MINI EXCAVATOR

Please indicate YES or NO if the machine offered can or cannot meet the desired configuration
Any "NO" must be clarified on a separate sheet if the bidder desires support for any alternate specification.

DESCRIPTION	COMPLY	YES / NO
WEIGHT:		
Minimum weight with all options no less than 12,000 lbs		
ENGINE:		
Four-stroke, four cylinder, water-cooled, wet sleeve, turbo charged diesel engine		
Open access tilt hood for engine		
Engine coolant block heater		
Single radiator cooling system		
Wet sleeve cylinder liners		
Diesel fuel thermal start-aid		
12-volt direct electric starting and charging system		
19 gallon fuel tank		
Fuel-Water seperator		
hand throttle		
Dry-type, dual element air cleaner with precleaner and automatic dust ejector		
Air cleaner service indicator		
Antifreeze with protection to -40 degrees fahrenheit		
Spin-on, full-flow oil filter; spin-on fuel filter		
Engine enclosures (side panels) with lockable side doors		
BACKHOE:		
Extendable Stick		
Excavator style boom		
Two handle pilot control S.A.E Controls		
Multi brand backhoe quick coupler		
Hydraulic Thumb for 24 inch bucket		
Outerbox extendible dipperstick for trench protection		
24 inch excavator bucket with teeth		
18 inch excavator bucket with teeth		
30 inch or greater smooth grading bucket		
Felco industries 18 x 32 semgented roller bucket		

DESCRIPTION
HYDRAULICS:

COMPLY YES / NO

ELECTRICAL SYSTEM & LIGHTS

[illegible]

WARRANTY
